

ZHEJIANG TIANYU ELECTRONIC CO.,LTD

Address: Huangyuan Village, Chunjiang Street, Yiwu City, Zhejiang, China 322000

Homepage: www.tianyupower.com

Tel: 0086-579-85384341 Fax: 0086-579-85384341

Email: sales@tianyupower.com Msn: tianyupower@hotmail.com

3000W Pure sine wave power inverter (TY-3000-S-12V)

Soft Start , External Fuses ,USB (Optional), Remote Control(Optional)

Model : TY-3000-S		TY-3000-S-12V
AC Output	Continuous power:	3000W
	Surge power:	6000W
	Max Constant Power Start :	3600W for 10 seconds
	Output Waveform	Pure Sine Wave (THD < 3%)
	Output Frequency	50Hz±0.1% or 60Hz±0.1% (Optional)
	AC Output Voltage	100~120VAC / 200~240VAC (Optional)
DC Input	DC Input Voltage	12V DC
	Voltage Range	10.8V-15.5V
	Low Voltage Alarm	10.8V± 0.2V
	Low Voltage Shut down	10.2V± 0.2V
	Over Voltage Shut down	15.5V±0.2V
	Over load shut down	3600W over 10 seconds
Converting Max. Efficiency		90% (Full Loading) / 95% (1/3 Loading)
No Load Consumption		< 0.9A
Protection	Over Thermal:	Shut Off Output Automatically, Temperature >75°C
	Short circuit protection:	Reverse Polarity (External Fuse)
	Cooling Fan automatically run	Temperature ≥45°C
Environment	Working temperature	-10°C ~+50°C
	Working humidity	20%~90% RH Non-Condensing
	Storage Temperature Range	-30°C ~+70°C
LED Indicator Light		Inverter, Fault
Packing	Inner Box Dimensions (mm)	530*320*230 mm
	Inner Box Weight (kg)	10 kg
	Carton Dimensions (mm)	555*340*250 mm
	Carton Weight (kg)	11 kg