

General Use AGM

VRLA AGM Series

GENERAL INFORMATION

UNIBAT General Use AGM series is designed for both stand-by or cyclic applications. It incorporates the latest AGM VRLA technology and excellent know-how. It is tested according to international standard IEC 60896-21, complies to defined requirements of IEC 60896-22, and classified for <33AH as “General Purpose” 6-9 Years & for >33AH as “Long Life” 10-12 Years Lifetime according to the EUROBAT 2015 guide.



The unique construction and sealing techniques of General Use AGM series guarantee leak proof operation in any position, with no adverse effect to capacity or service life.

Positive Plates : The positive plates are made of a grid frame of heavy duty lead-tin-calcium alloy and active material of porous lead dioxide.

Negative Plates : The negative plates are made of a grid frame of lead-tin-calcium alloy as well and with active material of spongy lead.

Separator : Plate separators are made of non-woven fabric of fine glass fibers and are chemically stable in the electrolyte sulfuric acid. The high porousness fully absorbs the electrolyte and prevents

shorting between positive and negative plates.

Terminals : The electrode terminals are protected due to both the structure that secures long adhesive - embedded paths and the use of strong epoxy material.

Electrolyte : They utilize an electrolyte suspension system consisting a high porosity, glass fiber material, which in conjunction with plates, totally absorbs the electrolyte.

Safety Valves : The incorporated built-in design controls gas generation and induces recombination of more than 99% of gases generated during float usage. Special safety release valves, designed to operate between 2 and 5 psi automatically reseal, preventing an excessive accumulation of gas inside the battery.

Container - Lid : The battery case is made of ABS material, is shock resistant and can be also available as flame retardant too.

APPLICATIONS

- UPS/EPS Systems
- Security & Fire Alarm Systems
- Emergency Lighting
- Telecom Power Supply
- Back up Power Supply
- Electronics
- Electric toys
- Medical Electronics
- Weighting Scales & Cash Registers

DESIGN FEATURES & BENEFITS

- Increase durability and deep cycle ability for heavy demand applications
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Spill proof / leak proof
- Multi-position usage
- Very good power to weight ratios
- Very high lead purity rate (higher than 99.994%)
- ABS case and cover V0 upon request

General Use AGM

VRLA AGM Series

RANGE SUMMARY

UNIBAT GENERAL USE AGM SPECIFICATION TABLE											
BATTERY TYPE	V	AH	DIMENSIONS				max. Charge Current	Recom. max. Discharge Current (5 sec)	WEIGHT	TERMINALS	
			L	W	H	T.H				TYPE	LAYOUT
			(mm)								
		C20								4-6 Years Lifetime	
1.3-6	6	1,3	97	24	52	58	0,26	20	0,26	F1	C
3.2-6	6	3,2	134	34	61	67	0,64	48	0,61	F1	C
4.5-6	6	4,5	70	47	101	107	0,70	40	0,69	F1	B
10.0-6	6	10	151	50	94	100	2,00	180	1,63	F1	C
12.0-6	6	12	151	50	94	100	2,40	180	1,78	F1	C
3.2-8	8	3,2	134	36	63	69	0,64	48	0,84	F1	E
1.3-12	12	1,3	97	43	52	58	0,36	13	0,53	F1	E
2.3-12	12	2,3	178	35	61	67	0,70	23	0,86	F1	C
3.3-12	12	3,3	134	67	61	67	0,80	33	1,23	F1	E
5.0-12	12	5	90	70	101	107	1,10	75	1,59	F1	C
6.0-12	12	6	151	52	94	99	1,20	90	1,82	F1	F
7.0-12	12	7	151	65	94	100	1,57	98	1,96	F1, F2	F
7.2-12	12	7,2	151	65	94	100	1,70	101	2,14	F2	F
7.5-12	12	7,5	151	65	94	100	2,25	105	2,60	F2	F
9.0-12	12	9	151	65	94	100	2,10	135	2,44	F1, F2	F
12-12	12	12	151	98	95	101	2,90	180	3,45	F1	F
18-12	12	18	181	77	167	167	4,13	270	5,00	M5	D
26-12	12	26	166	175	125	125	6,10	390	7,75	M5, M6	D
		C10								10 Years Lifetime	
33-12	12	33	195	130	155	166	9,90	330	10,00	M6-B	C
40-12	12	40	197	165	170	170	10,00	400	12,40	M6-B	D
55-12	12	55	229	138	208	211	14,00	550	16,00	M6-B	C
65-12	12	65	350	167	179	179	17,00	650	20,00	M6-B	C
80-12B	12	80	260	168	211	214	21,00	800	23,50	M6-B	C
80-12A	12	80	350	167	179	179	21,00	800	23,00	M6-B	C
100-12	12	100	330	171	214	220	27,00	1.000	28,20	M8	C
150-12	12	150	485	172	240	240	4,10	1.500	41,70	M8	C
200-12	12	200	522	238	218	221	53,00	2.000	58,50	M8	E



General Use AGM VRLA AGM Series

PERFORMANCE CURVES

Charge Characteristic Curves (25 °C)



4-6 Y Lifetime

10 Y Lifetime





Discharge Characteristic Curves (25 °C)

Charging Voltage vs Temperature



Self Discharge vs Capacity


Cycle Life vs D.O.D



General Use AGM


VRLA AGM Series

BATTERY DIMENSIONS



TERMINAL TYPES - LAYOUTS

TERMINAL TYPES



TERMINAL LAYOUTS

